



Products Show Hose Wire





Email: jonsen@yushengmax.com Mob.:+86 13963602511

Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China.



YUSHENG ENTERPRISE LIMITED

COMPANY PROFILE

YuSheng Enterprise Limited established in 2001, committed to rubber industry raw materials production and sales for more than 20 years.

After years of development, Yusheng has become a professional supplier of raw materials of rubber products, selling and serving tire and rubber products manufacturers in Europe, South America, Southeast Asia, India, Pakistan, the Middle East and other regions.

Yusheng is having more than 160+ stable and long-term manufacturing bases, which can provide one-stop raw material services for manufacturers in rubber industry. We sincerely invite rubber professionals from all over the world to join our global supply chain service system and become our partner to achieve win-win development.



Email: jonsen@yushengmax.com Mob.:+86 13963602511 Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China. Website: www.yushengmax.com



Production process



Email: jonsen@yushengmax.com Mob.:+86 13963602511

Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China.



Characteristics


It has good strength, toughness and fatigue property, and has uniform brass coating and good adhesive property of rubber.

Applications

As the framework material of the rubber hose, it can be used to reinforce the rubber hose. And also widely used in the coal industry, Engineering Machinery and petroleum industry.







Email: jonsen@yushengmax.com Mob.:+86 13963602511 Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China. Website: www.yushengmax.com



Specification

Speci .	toleranc -e (mm)	Breakin g strength (N) ≥	Elongati on at break (%) ≥	Tensile Strengt h (Mpa) ≥	Ratio of Knottin g tension (%)	Torsion (Times/ 360∘ L=100d) ≥	The number of breaking reverse bends (r=2.5mm) ≥	Bronze coating			
								Weigh t (g/kg) ≥	Cu/Copp er (%)	Cast (mm) ≥	Nose (mm) ≤
ф0.25m mHT	±0.01	135	1.6	2750	58	35	105	5±2	67.5±4	100	40
ф0.295 mmNT	±0.01	173	1.6	2450	58	37	95	5±2	68±4	100	40
ф0.38m mNT	±0.01	278	1.6	2450	58	34	60	5±2	67.5±4	100	40
ф0.50m mNT	±0.01 5	480	2.0	2450- 2750	55	60	35	5±2	68±4	100	40
ф0.56m mNT	±0.01	603	2.0	2450- 2750	55	60	30	4±2	68±4	120	40

Note: Special spec. can be customized by the requirement/sample from customers.

Email: jonsen@yushengmax.com Mob.:+86 13963602511


Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China.



Packing:

Use spool or wood core, and then use carton vacuum packing.







Email: jonsen@yushengmax.com Mob.:+86 13963602511 Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China. Website: www.yushengmax.com



Trustworthy Partner of Rubber Raw Materials

Email: jonsen@yushengmax.com Mob.:+86 13963602511

Add.: 6F Dong Sheng Plaza Wei Fang City, Shan Dong Province, China.